

# TXE1eco

## THE RELIABLE BASE TENSIONER PUMP



### **MANOMETER**

Easy pressure setup

### **7L OIL VOLUME**

For large or several simultaneously connected tools

### **OPERATION**

Via cable remote control

# EATURES

- ▶ Attractive price
- ▶ Fast & safe tensioning up to 1500bar
- Easy operation via cable remote control
- ▶ Stepless adjustable pressure thanks to manual adjustment valve
- ▶ Manage pressure with button
- ▶ Manual safety relief
- ▶ Resistant due to robust protective frame



PDF TO THE PRODUCT




The TXE1eco from PLARAD® is a robust and reliable basic pump for tensioning applications. The power unit is equipped with a powerful electric motor and can be effortlessly connected to large tensioners thanks to the 7L tank.


It offers a maximum operating pressure of 1500 bar and a flow rate of up to 3 l/min.


In addition, the pump has an integrated pressure gauge for easy reading and control of the pressure. The unit is easy to operate by remote control and is perfect for applications where no documentation is required.

# TXE1eco // data

Dimensions (WxHxD)	380 x 630 x 360 mm
Max. pressure	21,755 psi / 1,500 bar
Power supply	230V 50/60Hz // 110V 50/60Hz 400V 50Hz 460V 60Hz // 480V 60Hz
Power	1,1kW
Flow rate	0-1,740 psi / 0 - 120 bar ▶ 3.0 l/min
	1,740-21,755 psi / 120 - 1,500 bar ▶ max 0.35 l/min
Oil volume	1.8 gallon / 7 l
Weight	~80 pound / ~38 kg
Relief	electric + manual









630

