

Name	Geeignet für Suitable for	Drehmomentmodus Torque mode	Drehwinkelmodus Torque - Angle mode	Dokumentation Documentation	Betriebsart Operating mode	max. Druck max. pressure [bar]	max. Durchfluss max. flow		Motorleistung performance [kW]	Maße (LxBxH) dimensions (LxWxH) [mm]	Gewicht weight [kg]
							[l/min]	2 - stage Upgrade [l/min]			
XE1eco 10		x			Manuell	800	0,8	5,4	0,8	455x286x449	22
XE1eco 20		x			Manuell	800	1,2	8,0	1,1	500x343x465	29
XE1eco 30		x			Manuell	800	3,0	13,2	2,2	500x343x465	35
XE1power 10		x			Automatik	800	0,8	5,4	0,8	455x286x449	24
XE1power 20		x			Automatik	800	1,2	8,0	1,1	500x343x465	34
XE1power 30		x			Automatik	800	3,0	13,2	2,2	500x343x465	36
XE1docu 10		x		x	Automatik	800	0,8	5,4	0,8	455x286x449	24
XE1docu 20		x		x	Automatik	800	1,2	8,0	1,1	500x343x465	34
XE1docu 30		x		x	Automatik	800	3,0	13,2	2,2	500x343x465	36
XE1control 10		x	x	x	Automatik	800	0,8		0,8	455x286x449	26
XE1control 20		x	x	x	Automatik	800	1,2		1,1	500x343x465	31
XE1control 30		x	x	x	Automatik	800	3,0		2,2	500x343x465	35
XA1power		x			Automatik	800	1,0		0,5	275x184x360	10

DUAL XE1docu 20		x		x	Automatik	800/1500	1,2	8,0	1,1	500x343x465	40
DUAL XE1docu 30		x		x	Automatik	800/1500	3,0	13,2	2,2	500x343x465	42
DUAL XE1control 20		x	x	x	Automatik	800/1500	1,2		1,1	500x343x465	40

TXE1eco 20		x			Manuell	1500	0,35		1,1	380x360x630	38
TXE1docu 10		x		x	Automatik	1500	0,8		0,8	450x317x366	31
TXE1docu 20		x		x	Automatik	1500	1,0		1,1	500x343x465	39
TXE1docu 30		x		x	Automatik	1500	1,0		2,2	500x343x465	41

Aggregate in folgenden Spannungen erhältlich: 110V 50Hz, 110V 60Hz, 230V 50Hz, 230V 60Hz, 400V 50Hz, 400V 60Hz. Weitere auf Anfrage.
Units available in the following voltages: 110V 50Hz, 110V 60Hz, 230V 50Hz, 230V 60Hz, 400V 50Hz, 400V 60Hz. Others on request.
Alle Angaben ohne Gewähr | All data without guarantee

XE1power



XA1power



TXE1docu

